

TOILET D-ODOR

Vault Toilet Deodorant

Form: Liquid
Color: Dark Blue
Odor: Bubblegum
pH: 6.0 – 7.0
Solubility (in water): Soluble
(in mineral spirits): Insoluble
VOC Content (% by weight): <3.0%
Flash Point (ASTM D-7821): 150°F
Specific Gravity: 0.99 ± 0.05 g/cm³
Density: 8.26 ± 0.05 lbs/gal
Storage Stability (at 70°F): 1 year

<u>Ingredients</u>	<u>C.A.S. #</u>
Water.....	7732-18-5
Alkyl dimethyl benzyl ammonium chloride	68391-01-5
Alkyl dimethyl ethylbenzyl ammonium chloride	68956-79-6
Poly (oxyethylene) nonylphenol.....	9016-45-9
Ethanol.....	64-17-5

Safe to use in...

- **Tank Type Chemical Toilets**
- **Recirculating Toilets**
- **Holding Tank Systems**
- **Portable Tank Toilets**

Neutralizes objectionable waste odors and retards the return of these odors as well as noxious gases.

DIRECTIONS:

PORTABLE TOILETS: For summer use, add 8 to 12 ounces of TOILET D-ODOR per 60 gallons of toilet capacity. During winter or colder periods, use 3 to 6 ounces per 60 gallons of toilet capacity.

MARINE AND RV TOILETS: Add 16 ounces with sufficient water to cover the bottom of holding tank.

Note: Very warm weather, long time periods between pump-out, and heavy loading may require more treatment to adequately control odors. This product should not be used in septic systems or permanent pit toilets, as it will prevent bacterial digestion of wastes. Treated waste should be disposed of through municipal treatment plants -- do not apply to farmland.

HMIS			NFPA		
	Severe	4	Extreme		
Health	Serious	3	High	Health	2
Flammability.....	Moderate	2	Moderate	Flammability.....	2
Reactivity.....	Slight	1	Slight	Reactivity.....	0
Personal Protection	Minimal	0	Insignificant	Special Precautions.....	None