

CONCENTRATED LIQUID LOWERS pH WITHOUT CLOUDING

DANGER

May be corrosive to metals. Causes severe skin burns and eye damage.

May cause respiratory irritation.

KEEP OUT OF REACH OF CHILDREN
NET CONTENTS: ■ 1 ■ 5 ■ 20 ■ 35 ■ 55 Gallon(s)





PO BOX 245013 MILWAUKEE, WI 53224 800.776.7192 www.sharecorp.com



Keep only in original container. Do not breathe mist, spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear eye protection, protective clothing, protective gloves. Wash contaminated clothing before reuse.

IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
IF ON SKIN (OR HAIR): Take off immediately all
contaminated clothing, Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep
comfortable for breathing

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER. Call a doctor, a POISON CENTER if you feel unwell.

Absorb spillage to prevent material damage.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Store in corrosive resistant container with a resistant inner liner.

For industrial and commercial use only. For additional information, see Safety Data Sheet.

WARNING:

This product can expose you to 1,4-dioxane which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Dry skin, scale deposits on filter, pump pool walls and hazy water can be attributed to excessive alkalinity in swimming pool waters. **ACID pH ADJUSTMENT** is the most convenient approach to lowering the pH of pool water and neutralizing alkalinity. The liquid form eliminates the additional storage and dosage problem frequently encountered with pool pH and keeps alkalinity levels under control with **ACID pH ADJUSTMENT**.

DIRECTIONS

The amount required to lower the pH depends on the water's natural buffing capacity. Add 1 to 2 quarts directly to the pool at a point of strong agitation. Do not add to the skimmer or vacuum. Allow 15 to 20 minutes for thorough mixing, then retest the pH to see if it falls within acceptable limits (7.2 to 7.8) If pH tests greater than 7.8, repeat application.

NFPA® Ratings

Health: 1; Flammability: 0; Reactivity: 0

Contains/CAS Number:

Water (7732-18-5); Hydrochloric Acid (7647-01-0); Linear Alcohol Ethoxylate (34398-01-1); Tallow Alkyldiamine Ethoxylate (61790-85-0); Surfactant (Proprietary).

Dispose of contents/container to comply with local regional/national/international regulations.



Please Recycle

0140.041520