

FREEZY

Biodegradable Ice Melter



Form: Liquid

Color: Colorless

Odor: None

pH: 10.0 – 11.0

Solubility (in water): Soluble
(in mineral spirits): Insoluble

VOC Content (% by weight): <1.0

Flash Point (ASTM D-7821): >200° F

Specific Gravity: 1.28 g/cm³

Density: 10.68 lbs /gal

Storage Stability (at 70°F): 1 year

<u>Ingredients</u>	<u>C.A.S. #</u>
Potassium Acetate	127-08-2
Water	7732-18-5
Triethanolamine	102-71-6

For Use on...	
•	Sidewalks (concrete or asphalt)
•	Runways (concrete or asphalt)
•	Ramps and stairs
•	Aluminum and steel
•	Rubber and plastic
•	Locks, hinges and controls
•	Painted surfaces
•	Terrazzo
•	And more....

DIRECTIONS:

FREEZY is a ready-to-use liquid that should be applied at full strength. Apply liquid solution by any means of spraying, pouring or swabbing.

Anti-Icing: Use to pre-treat surface to prevent accumulation and bonding of snow and ice. Apply before winter storm arrives by wetting surface at a rate of a 1/2 gallon per 1,000 square feet.

Deicing: Application rates may vary depending on ice thickness and outdoor temperatures.

Thin ice: Apply at a rate of 1 gallon per 1,000 square feet.

For ice up to 1" thick: Apply at a rate of 3 gallons per 1,000 square feet.

NOTE: New concrete must be cured a minimum of 90 days prior to applying FREEZY.

HMIS			NFPA		
		Severe 4	Extreme		
Health.....	1	Serious 3	High	Health.....	1
Flammability.....	0	Moderate 2	Moderate	Flammability.....	0
Reactivity.....	0	Slight 1	Slight	Reactivity.....	0
Personal Protection.....	X	Minimal 0	Insignificant	Special Precautions.....	None