



Do not use on or near clear plactic. Do not use on steering wheels, pedals and other instrumentation where slipperiness may present a hazard. Offer empty container for recycling. If recycling is not available, discard container in trash.

Disposal:

Orien empts to dtailer for recycling. If recycling is not available discard container in trash.

For industrial and commercial use only.

Eoradditional information, see Safety Data Sheet.

DIRECTIONS:

- 1. Place trigger sprayer on bottle
- 2. Hold bothe 10 to 12 inches from surface to be treated.

 3. ADOLV a light mist of Plexi Polish over the entire
- sunface evenly, wiping inmediately with a soft cloth.
- 4. Turn cloth over and buff surface to reveal a brilliant shine.
- 5. Do not allow to dry before wiping

Golf Cart Windsbield Application:

For best results, follow instructions above, applying **PLEXH-POLISH** to both sides of the cart windshield.

NFPA® RATINGS:

Health: 0; Flammability: 0; Reactivity: 0

INGREDIENTS/CAS #:

Water (7732-18-5); Polydimethylsiloxane (63148-62-9); Linear Alcohol Ethoxylate (34398-01-1); Triethanolamine (102-71-6); Ethoxylated Isoalcohols (78330-21-9).



Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com

0295.110416