

# LO-FOAM STEAM EXTRACTOR CONCENTRATE

## Carpet Steam Extraction Shampoo

**Form:** Liquid

**Color:** Clear, Light, Blue/Green

**Odor:** Detergent

**pH:** 10.75-11.75

**Solubility ( in water):** Soluble  
**(in mineral spirits):** No data available

**VOC Content (% by wt):** <0.5

**Flash Point (Closed Cup):** >200°F

**Specific Gravity:** 1.05 g/ml

**Density:** 8.76 lbs/gal

**Storage Stability (at 70°F):** 1 year

<u>Ingredients</u>	<u>C.A.S. #</u>
Water.....	7732-18-5
C5-C9 Alkyl Amphopropionate..	70983-43-6
Sulfosuccinamate .....	38916-42-6
Tetrapotassium Pyrophosphate .....	7320-34-5
Tetrasodium EDTA.....	64-02 8

<b>Other Uses...</b>
• <b>Car and Truck Wash</b>
• <b>Coil Cleaner</b>
• <b>Kitchen Degreaser</b>
• <b>Laundry Pre-Soak</b>
• <b>Water Filter Cleaner</b>
• <b>Vinyl Cleaner</b>

**DIRECTIONS:** Use 2 to 4 ounces of LO-FOAM STEAM EXTRACTOR CONCENTRATE per gallon of water in extractor tank. Follow manufacturer's directions for machine's use.

<b>HMIS®</b>			<b>NFPA®</b>		
	Severe	4	Extreme		
Health .....	Serious	3	High	Health.....	1
Flammability .....	Moderate	2	Moderate	Flammability.....	0
Reactivity.....	Slight	1	Slight	Reactivity.....	0
Personal Protection.....	Minimal	0	Insignificant	Special Precautions.....	None