



RELEASE EASE

ASPHALT RELEASE AGENT

Inhibits Asphalt Adhesion to Truck Beds and Other Equipment
Easy To Apply • Easy On The Environment

DANGER

May be corrosive to metals. Causes skin irritation.
May cause an allergic skin reaction. Causes serious eye damage.
Suspected of causing cancer.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: ■ 1 ■ 5 ■ 20 ■ 35 ■ 55 Gallon(s)

RELEASE EASE



PO BOX 245013
MILWAUKEE, WI 53224
800.776.7192
www.sharecorp.com



DANGER:

May be corrosive to metals. Causes skin irritation.
May cause an allergic skin reaction. Causes serious eye damage. Suspected of causing cancer.

PREVENTION:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep only in original container. Avoid breathing mist, spray. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Wear eye protection, protective clothing, protective gloves. Take off contaminated clothing and wash it before reuse.

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation or rash occurs: Get medical advice/attention.

If exposed or concerned: Get medical advice/attention. Immediately call a doctor, a POISON CENTER.

Absorb spillage to prevent material damage.

Store locked up. Store in corrosive resistant container with a resistant inner liner.



For industrial and commercial use only.

For additional information, see Safety Data Sheet.

Please Recycle.

RELEASE EASE is an asphalt release coating that provides a molecular film that prevents the sticking and adhesion of asphalt. **RELEASE EASE** produces a thin heat resistant shield that provides a "slick" surface such that hot, sticky asphalt simply rolls off. **RELEASE EASE** also provides protection for your equipment surfaces. This unique coating stays in place providing protection from asphalt deposits and from the damaging effects of rust and corrosion. **RELEASE EASE** has also been tested and approved for use by the Georgia and Maryland Departments of Transportation.

DIRECTIONS FOR USE:

RELEASE EASE is easy to use. Simply mix 1-1/2 quarts of **RELEASE EASE** in 2 gallons of water. Spray equipment thoroughly with solution. Agitate solution during use. Allow equipment to dry before putting into service. For best performance, equipment should be treated before each use.

NFPA® RATINGS:

Health: 2; Flammability: 0; Reactivity: 0

INGREDIENTS/CAS #:

Water/7732-18-5; Distilled Tall Oil/8002-26-4; Tetrasodium Ethylenediamine Tetraacetate/64-02-8; Potassium Hydroxide/1310-58-3; Sodium Hydroxyacetate/2836-32-0

Dispose of contents/container to comply with local/regional/national/international regulations.

WARNING:

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

0366.060915