Safety Data Sheet



SECTION 1: Product and company identification

Product name	: Corkscrew
Use of the substance/mixture	: Lift Station Degreaser
Product code	: 038103
Company	: Share Corporation P.O. Box 245013 Milwaukee, WI 53224 - USA T (414) 355-4000
Emergency number	: Chemtrec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

. . . .

. .

Flam. Liq. 3 H226 Skin Irrit. 2 H315 Skin Sens. 1 H317 Asp. Tox. 1 H304 Full text of H statements : see section 16

2.2. Label elements	
GHS-US labeling	
Hazard pictograms (GHS-US)	GHS02 GHS07 GHS08
Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	: Flammable liquid and vapor May be fatal if swallowed and enters airways Causes skin irritation May cause an allergic skin reaction
Precautionary statements (GHS-US)	 Keep away from heat, sparks, open flames No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof ventilating equipment Use only non-sparking tools Take precautionary measures against static discharge Avoid breathing mist, vapors Wash thoroughly after handling Contaminated work clothing must not be allowed out of the workplace Wear eye protection, protective clothing, protective gloves If swallowed: Immediately call a POISON CENTER, a doctor If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower Do NOT induce vomiting If skin irritation or rash occurs: Get medical advice/attention Take off contaminated clothing and wash it before reuse In case of fire: Use foam, carbon dioxide, dry chemical to extinguish Store in a well-ventilated place. Keep cool Store locked up Dispose of contents/container to comply with local/regional/national/international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US) Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substance Not applicable

Safety Data Sheet



3.2. Mixture			
Name	Product identifier	%	GHS-US classification
(+)-limonene	(CAS No) 5989-27-5	85-100	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304

A specific chemical identity and/or percentage of composition has been withheld as a trade secret. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general	: If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	Wash with plenty of soap and water. Take off immediately all contaminated clothing and wash it before reuse. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	 Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Immediately call a poison center or doctor/physician. Do NOT induce vomiting.
4.2. Most important symptoms and effect	ts, both acute and delayed
Symptoms/injuries	: If you feel unwell, seek medical advice.
Symptoms/injuries after inhalation	: Irritation of the respiratory tract.
Symptoms/injuries after skin contact	: Causes skin irritation. May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.
Symptoms/injuries after eye contact	: Direct contact with the eyes is likely irritating.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. Risk of aspiration pneumonia.
Chronic symptoms	: Red skin. Swelling of the skin. Skin rash/inflammation. Itching.

4.3. Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures	
5.1. Extinguishing media Suitable extinguishing media Unsuitable extinguishing media	: ABC powder. Alcohol-resistant foam. Carbon dioxide. : Do not use a water jet since it may cause the fire to spread.
5.2. Special hazards arising from the subst	ance or mixture
Fire hazard	 DIRECT FIRE HAZARD. Flammable. Gas/vapour flammable with air within explosion limits. INDIRECT FIRE HAZARD. May build up electrostatic charges: risk of ignition. May be ignited by sparks. Reactions involving a fire hazard: see "Reactivity Hazard".
Explosion hazard	: DIRECT EXPLOSION HAZARD. Gas/vapour explosive with air within explosion limits. INDIRECT EXPLOSION HAZARD. may be ignited by sparks. Reactions with explosion hazards: see "Reactivity Hazard".
Reactivity	: Reacts with (strong) oxidizers. Reacts with (some) acids. Reacts with (some) halogens compounds. Upon combustion: CO and CO2 are formed.
5.3. Advice for firefighters	
Firefighting instructions	 Cool tanks/drums with water spray/remove them into safety. Take account of environmentally hazardous firefighting water. Use water moderately and if possible collect or contain it.
Protection during firefighting	: Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures			
6.1. Personal precautions, protective equip	nent and emergency procedures		
General measures	: No flames, No sparks. Eliminate all sources of ignition.		
6.1.1. For non-emergency personnel			
Protective equipment	: Protective goggles. Gloves. Protective clothing.		
Emergency procedures	: Mark the danger area. Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Keep containers closed. Wash contaminated clothes. In case of reactivity hazard: consider evacuation. Evacuate unnecessary personnel. Avoid contact with skin, eyes and clothing. Ventilate spillage area.		
6.1.2. For emergency responders			
Protective equipment	: Equip cleanup crew with proper protection.		

Safety Data Sheet



balloty Balla Onloot	
Emergency procedures	: Stop leak if safe to do so. Stop release. Ventilate area.
6.2. Environmental precautions	
Avoid release to the environment.	
6.3. Methods and material for conta	inment and cleaning up
For containment	Contain released substance, pump into suitable containers. Plug the leak, cut off the supply. Dam up the liquid spill. Provide equipment/receptacles with earthing. Do not use compressed air for pumping over spills. Heating: dilute combustible gas/vapour with water curtain.
Methods for cleaning up	Take up liquid spill into absorbent material, e.g.: sand, earth, vermiculite. Scoop absorbed substance into closing containers. Carefully collect the spill/leftovers. Damaged/cooled tanks must be emptied. Do not use compressed air for pumping over spills. Clean contaminated surfaces with an excess of water. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4 .	Reference to other sections	
No a	dditional information available	

SECTION 7: Handling and storag	e	
7.1. Precautions for safe handling		
Precautions for safe handling		: Comply with the legal requirements. Remove contaminated clothing immediately. Clean contaminated clothing. Thoroughly clean/dry the installation before use. Do not discharge the waste into the drain. Do not use compressed air for pumping over. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Observe very strict hygiene - avoid contact. Keep container tightly closed. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection. Ground/bond container and receiving equipment. Use only non-sparking tools. Use explosion-proof equipment. Take precautionary measures against static discharge.
Hygiene measures		: Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.
7.2. Conditions for safe storage, includin	g any	y incompatibilities
Technical measures	:	Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.
Storage conditions	:	Keep container tightly closed.
Incompatible materials	:	Keep only in the original container in a cool, well ventilated place away from: sparks, open flames, excessive heat.
Heat-ignition	:	KEEP SUBSTANCE AWAY FROM: ignition sources. heat sources.
Prohibitions on mixed storage	:	KEEP SUBSTANCE AWAY FROM: oxidizing agents.
Storage area	:	Store away from heat. Store in a cool area. Store in a dry area. Store in a well-ventilated place.
Special rules on packaging	:	Keep only in original container. meet the legal requirements.
Packaging materials	:	No data available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Personal protective equipment

Use appropriate personal protective equipment when risk assessment indicates this is necessary. Gloves. Safety glasses. Protective goggles. Protective clothing. :



SECTION 9: Physical and	chemical properties	
9.1. Information on basic physic	al and chemical properties	
Physical state	: Liquid	
Appearance	: Clear, red colored liquid.	
Odor	: Citrus scent	
Odor threshold	: No data available	
рН	: No data available	
Melting point	: No data available	
Freezing point	: No data available	

Safety Data Sheet

<u> </u>	
Boiling point	: 175.5 - 176 °C
Flash point	: 115 °F Closed Cup
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 0.84 g/ml
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: 237 °C
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: <= 20 cSt
Viscosity, dynamic	: No data available
VOC content	: > 90 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with (strong) oxidizers. Reacts with (some) acids. Reacts with (some) halogens compounds. Upon combustion: CO and CO2 are formed.

10.2. Chemical stability Stable under normal conditions.

10.3. Possibility of hazardous reactions Refer to section 10.1 on Reactivity.

10.4. Conditions to avoid No additional information available

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Floating Lift Station Degreaser	
LD50 oral rat	4400 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
(+)-limonene (5989-27-5)	
LD50 oral rat	4400 mg/kg body weight (Rat; OECD 423: Acute Oral Toxicity – Acute Toxic Class Method; Literature study; > 2000 mg/kg bodyweight; Rat; Read-across)
LD50 dermal rabbit	> 5000 mg/kg body weight (Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
ATE CLP (oral)	4400.000 mg/kg body weight
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
(+)-limonene (5989-27-5)	
IARC group	3 - Not Classifiable



Safety Data Sheet



Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: Irritation of the respiratory tract.
Symptoms/injuries after skin contact	: Causes skin irritation. May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.
Symptoms/injuries after eye contact	: Direct contact with the eyes is likely irritating.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. Risk of aspiration pneumonia.
Chronic symptoms	: Red skin. Swelling of the skin. Skin rash/inflammation. Itching.

SECTION 12: Ecological information

2.1. Toxicity				
Floating Lift Station Degreaser				
LC50 fish 1	720 μg/l			
EC50 Daphnia 1	0.36 mg/l			
LC50 fish 2	702 μg/l			
(+)-limonene (5989-27-5)				
LC50 fish 1	720 μg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Pimephales promelas; Flow- through system; Fresh water; Experimental value)			
EC50 Daphnia 1	0.36 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)			
Threshold limit algae 1	150 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Desmodesmus subspicatus; Static system; Fresh water; Read-across)			
2.2. Persistence and degradability				
(+)-limonene (5989-27-5)				
Persistence and degradability	Readily biodegradable in water. Forming sediments in water. Adsorbs into the soil.			
ThOD	3.29 g O□/g substance			
2.3. Bioaccumulative potential				
(+)-limonene (5989-27-5)				
BCF fish 1	864.8 - 1022 (BCF; Pisces)			
Log Pow	4.38 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 37 °C)			
Bioaccumulative potential	Potential for bioaccumulation ($4 \ge Log$ Kow ≤ 5).			

SECTION 13: Disposal considerat	ions
13.1. Waste treatment methods	
Waste disposal recommendations	Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Recycle by distillation. Incinerate under surveillance with energy recovery. Do not discharge into surface water.
Additional information	: LWCA (the Netherlands): KGA category 03. Hazardous waste according to Directive 2008/98/EC.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport document description	: UN2319 Terpene hydrocarbons, n.o.s., 3, III
UN-No.(DOT)	: UN2319
Proper Shipping Name (DOT)	: Terpene hydrocarbons, n.o.s.
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT)

Safety Data Sheet

SHARE CORP

3	- Flammable liquid
0	

Packing group (DOT)	: III - Minor Danger
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Special Provisions (49 CFR 172.102)	: B1,IB3,T4,TP1,TP29
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A
Additional information	
Other information	: When transported by ground in non-bulk containers, this product utilizes the exception found under 49 CFR 173.150.
ADR	
Tunnel restriction code (ADR)	: D/E
Transport by sea No additional information available	
Air transport	
No additional information available	

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm.

SECTION 16: Other information

Training advice

: Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction

NFPA health hazard	:	2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.	
NFPA fire hazard	:	2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.	
NFPA reactivity	:	0 - Normally stable, even under fire exposure conditions, and are not reactive with water.	•



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.