## **CORKSCREW**

## Floor Drain Maintainer



Form: Liquid

Color: Reddish-Orange

**Odor:** Citrus

pH: N/A

**Solubility (in water):** Insoluble **(in mineral spirits):** Soluble

**VOC Content (% by weight):** >90.0

Flash Point (ASTM D-7821): 115°F

Specific Gravity: 0.84 g/cm<sup>3</sup>

**Density:** 7.01 lbs/gal

Storage Stability (at 70°F): 1 year

IngredientsC.A.S. #d-Limonene.5989-27-5Red Dye.No CAS Number

## Use in...

- Drains
- · Garbage Disposals
- Dumpsters
- Trash Compactors
- Grease Trap Maintainer
- Waste water Treatment Facilities
- Restaurants
- Kitchens

**DIRECTIONS:** Preventative maintenance programs that use CORKSCREW weekly (or more frequently) keep drains and grease traps free flowing and fresh smelling. To use, add 3 to 4 ounces to each drain, let stand for 10 minutes, and then flush with hot water. To open slow drains, add 1 pint directly to the drain, let stand for 30 minutes, then flush with hot water.

HMIS			,	NFPA
	Severe	4	Extreme	
Health1	Serious	3	High	Health1
Flammability2	Moderate	2	Moderate	Flammability2
Reactivity0	Slight	1	Slight	Reactivity0
Personal ProtectionX	Minimal	0	Insignificant	Special PrecautionsNone