

# SILICONIZED SNOW PLOW COATING

## Snow Release Agent

**Form:** Liquid

**Color:** Water White

**Odor:** Lemon

**pH:** N/A

**Solubility (in water):** Insoluble  
**(in mineral spirits):** Soluble

**VOC Content (% by weight):** 90.0

**Flash Point (ASTM D-7821):** 103°F

**Specific Gravity:** 0.79 g/cm<sup>3</sup>

**Density:** 6.59 lbs/gal

**Storage Stability (at 70°F):** 1 year

<u>Ingredients</u>	<u>C.A.S. #</u>
Mineral Spirits .....	64742-88-7
Dimethylpolysiloxane .....	63148-62-9
Perfume Lemon.....	No CAS Number

<b>Other Uses...</b>	
•	<b>Conduit Lubricant</b>
•	<b>Brick Protector</b>
•	<b>Wall Coating</b>
•	<b>Graffiti Inhibitor</b>
•	<b>Water Proofer</b>
•	<b>Reflective Sign Coating</b>
•	<b>Asphalt Release Agent</b>
•	<b>Concrete Truck Protector</b>

**DIRECTIONS:** Apply SILICONIZED SNOW PLOW COATING before a snow removal period. If reapplied at the end of each work period, SILICONIZED SNOW PLOW COATING will help protect equipment from rust and corrosion during periods of inactivity. Plow blades can be put into service immediately after coating but a drying time of 20 to 40 minutes is recommended for maximum durability.

<b>HMIS</b>			<b>NFPA</b>		
	Severe	4	Extreme		
Health .....	Serious	3	High	Health.....	1
Flammability.....	Moderate	2	Moderate	Flammability.....	2
Reactivity.....	Slight	1	Slight	Reactivity.....	0
Personal Protection.....	Minimal	0	Insignificant	Special Precautions.....	None