SHARE CORP

FAST ACTING ICE MELT PELLETS FOR USE ON ALL TRAFFIC AREAS

PELLET DEICER quickly melts ice and packed snow from sidewalks, driveways, steps, porches, parking lots, loading docks, ramps, drain pipes and eaves. PELLET DEICER is much more effective than ordinary salt or sand - it melts ice even at -50°F, and won't harm skin, clothing or lawns when used as directed.

EYE: May cause moderate to severe eye irritation with corneal injury, which may be slow to heal. When dissolving, the heat produced may cause more intense effects as well as thermal burns.

IF IN EYES: Irrigate with flowing water immediately and continuously for 15 minutes. Consult medical personnel.

SKIN CONTACT: Short single exposure not likely to cause significant skin irritation. Prolonged or repeated exposure may cause skin irritation, even a burn. May cause more severe response if skin is damp and/ or abraded, or if material is confined to skin. When dissolving, the heat produced may cause more intense effects as well as thermal burns. DOT classification. Non-corrosive.

IF ON SKIN: Wash off in flowing water or s

This material does not burn. If exposed to fire from another source, use suitable extinguishing agent to that fire

WARNING: This product when used in adveous formulations with a chemical exidizer such as ozone) may react to form calcium bromate a chemical known to the State of California to cause cancer.

KEEP OUT OF REACH OF CHILDREN.

For industrial and commercial use only. For additional information, see Safety Data Sheet.

Comply with federal, state, and local laws, regulations and procedures when storing this product. Store in a tightly closed container. Store away from incompatible

materials. Do not store in attic, upper floors or any area where leaking of contents could cause damage.

DISPOSAL: Offer empty containst for recycling. If recycling is not available discard container in trash.

SPECIAL PRECAUTIONS TO BE TAKEN WANDLING AND STORAGE: A Cide by a corpologied skin contact. ALWAYS USE COOL WATER TEMPERATURE LESS THAN 80°F, 27°C). WHEN DESOLVING CALCIUM CHLORIDE. HEAT DEVELOPED BY SOLUTION IS VERY HIGH DURING BUSSOLVING AND MIXING. When exposed to the attraction of the company of the c

DIRECTIONS: Sprinkle PELLET DEICER evenly over corp packed snow, allow it to act for several minutes, then remove melted slush. PELLET DEICER is not corresive and is safe to use on concrete, brick, cement, classtone and asphalt. However, spalling or flaking of these surfaces may occur due to natural deterioration from freeze/thaw cycles. While such instances are rare, they involve factors over which the manufacturer has no control, and the use of PELLET DEICER must be at the user's risk.

NOTE: PELLET DEICER should not be used on concrete less than one year old and should not be used on concrete with exposed aggregate, precast steps.

NFPA* RATING

Health: 1, Flammability: 0, Reactivity: 0



Dioaco Docuel

INGREDIENTS/CAS#

Calcium Chloride (010043-52-4); Sodium Chloride (007647-14-5); Potassium Chloride (007447-40-7); Water (007732-18-5)

0600.042815

Net Contents: 50 ■ 80 ■ 100 ■ Pounds