

FOAMING SEWER CLEANER & DEGREASER

Concentrated Foaming Sewer Degreaser

Form: Liquid

Color: Colorless

Odor: Mild

pH: N/D

Solubility (in water): Soluble
(in mineral spirits): Insoluble

VOC Content (% by weight): <4.0

Flash Point (ASTM D-7821): N/A

Specific Gravity: 1.00 ± 0.05 g/cm³

Density: 8.35 ± 0.05 lbs/gal

Storage Stability (at 70°F): 1 year

Good For...
• Animal Fats
• Vegetable Fats
• Oil
• Organic Matter

Ingredients

C.A.S. #

Water	7732-18-5
Linear Alcohol Ethoxylates	34398-01-1
Ethoxylated Alkyl Amines	68478-95-5
Amine Oxide	68478-65-9
5,5-Dimethylhydantoin.....	77-71-4

DIRECTIONS: Not recommended for household use. In a high pressure jet truck dilute 1 gallon of FOAMING SEWER CLEANER & DEGREASER in 100 gallons of water to treat approximately 100 feet of sewer pipe. Jet spray the FOAMING SEWER CLEANER & DEGREASER upstream from the affected pipe. Allow FOAMING SEWER CLEANER & DEGREASER 10 – 15 minutes to liquefy grease before jet spraying and retrieval.

The jet sprayer pressure should be set to maximum PSI and reel speed. Turn the water pressure off after the jet sprayer hose has been stopped at the upstream manhole. Wait 10 minutes and the grease will be homogenized.

For best results, use a rotating jet sprayer nozzle.

Treat any excess foaming with 2 to 5 ounces of FOAM MASTER per gallon of solution.

HMIS			NFPA		
	Severe	4	Extreme		
Health.....	Serious	3	High	Health	1
Flammability	Moderate	2	Moderate	Flammability	0
Reactivity	Slight	1	Slight	Reactivity	0
Personal Protection	Minimal	0	Insignificant	Special Precautions.....	None