

SEWER Compound XXX



**HIGH HEAT GENERATION WITH
MAXIMUM TURBULENCE
NON-FLAMMABLE • FAST ACTING**

EFFECTIVE • EFFICIENT

DANGER: POISON/CORROSIVE

KEEP OUT OF REACH OF CHILDREN. CAUSES SEVERE
SKIN BURNS AND EYE DAMAGE. SEE BACK PANEL FOR
ADDITIONAL PRECAUTIONS.

NET CONTENTS: 50 LBS (22.7 KG)



KEEP OUT OF REACH OF CHILDREN. READ LABEL
AND SDS BEFORE USE. CAUSES SEVERE SKIN BURNS
AND EYE DAMAGE. MAY BE CORROSIVE TO METALS.
Do not breath dusts. Wash hands and face thoroughly
after handling. Wear protective gloves, face mask,
splash proof goggles and other protective clothing.
Keep only in original container.

FIRST AID:

IF SWALLOWED: Rinse mouth. Do NOT induce
vomiting.

IF ON SKIN (OR HAIR): Take off immediately all
contaminated clothing. Rinse skin with water/shower.
Wash contaminated clothing before reuse.

IF IN EYES: Rinse cautiously with water for several
minutes. Remove contact lenses, if present and easy to
do. Continue rinsing. Immediately call a poison center
or a physician.

IF INHALED: Remove person to fresh air and keep
comfortable for breathing. Immediately call a poison
center or a physician.

Dispose of contents/container to comply with local/
regional/national/international regulations.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

**TO BE USED BY TRAINED PERSONNEL ONLY,
NOT FOR HOMEOWNER USE.**

SEWER COMPOUND XXX is specially formulated to generate
maximum heat and turbulence rapidly upon contact with water.
It will liquefy, emulsify, dissolve and loosen animal and
vegetable fats and oils, hair, paper, organic matter and many
other materials that tend to clog drains and sewer lines.
It will not damage pipes, drains, or sewer lines.

SEWER COMPOUND XXX is specifically formulated to reduce
the release of flammable gases or vapors when used according
to directions to remove normal sewer and drain obstructions.
**AVOID SMOKING WHEN USING SEWER COMPOUND XXX
COMPOUND. DO NOT THROW LIGHTED CIGARETTES OR
MATCHES INTO MANHOLES WHILE TREATING. SEWER
COMPOUND XXX** also contains a blend of highly visible tracing
dyes for observing the effects of the use of the product.

DIRECTIONS: Wear protective gloves, face mask, splash proof
goggles; and other protective clothing to avoid eye or skin
contact.

Pour small amount into drain at manhole opening making sure all
precautions are taken to avoid injury. After 15 minutes run plenty
of water through drain. Use sewer solvent at regular intervals to
keep sewers open. Do not stand over opening after pouring in
the solution.

**DO NOT ADD HOT WATER. DO NOT USE AROUND OPEN FLAME.
WARNING: CARELESS USE CAN CAUSE SEVERE BURNS TO SKIN
AND EYES.**

EXPOSURE: Severity of injury depends largely on product concen-
tration and duration of exposure. Immediate action is necessary to
limit severity of injury. Can cause minor irritation to severe burns
and tissue damage to exposed areas of the body. May be harmful
or fatal if swallowed.

NFPA® Ratings:

Health: 3; Flammability: 0; Reactivity: 1; Maximum Personal
Protection; D.

Contains/CAS Number:

Sodium Hydroxide (1310-73-2); Sodium Nitrate (7631-99-4);
Sodium Chloride (7647-14-5); Aluminum (7429-90-5).

0619.091517



Please Recycle.