

POOL & SPA CHI

PREVENTS CHLORINE LOSS CAUSED BY THE SUN. HELPS REDUCE CHLORINE USAGE.

WARNING

Causes serious eye irritation.

PREVENTION

Wash thoroughly after handling. Wear ev protection, protective clothing, protective

IF IN EYES: Rinse cautiously with water minutes. Remove contact lenses, if present a to do. Continue rinsing

If eye irritation persists: Get medical ag Call a poison center or doctor if you

DISPOSAL: Offer emoty container for recycling. If

recycling is not available, discard container in trash.

KEEP OUT OF REACH OF CHILDREN

For industrial and

For additional inform Safety Data Sheet.

INGRÈDIÈNTS/CAS#

lammability: 1; Reactivity: 0

SUN SHIELD prolongs the effective life of chlorine by reducing loss caused by the sun. The sun's UV rays deplete the free chlorine in the water; by slowing this depletion rate, less chlorine will be used. The abilizer level should be maintained between 30-50 ppm.

DIRECTIONS

Use 3lbs. of **SUN SHIELD** per 10,000 gallons of pool water to raise stabilizer level by 30 ppm. Shut the pool system off. Turn off the main drain if there is one. If the pool has multiple skimmers, shut all but one. Add the precisely measured amount of **SUN SHIELD** into a bucket of water and mix thoroughly to make a slurry. Remove both the pump and the skimmer basket. Turn the system back on. Very slowly pour the bucket of water and stabilizer slurry into the skimmer that is pulling water down into the pump. Shut the system off again. Replace both baskets. Start system back up. Keep the water circulating continuously for 24 hours after addition. Do not backwash filter for at least 48 hours after application. Test stabilizer level once a month and always test for current stabilizer levels before adding SUN SHIELD.



Please Recycle.

0695.042315

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com