



TRIDENT

WATER TREATMENT

BOILERPRO H PLUS

HARD WATER BOILER TREATMENT

SUPERIOR PROTECTION IN HARD WATER SYSTEMS
CONTAINS AN OXYGEN SCAVENGER & STEAM LINE TREATMENT

DANGER

Causes severe skin burns and eye damage.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 1 5 20 35 55 Gallon(s)

TRIDENT

WATER TREATMENT

BOILERPRO H PLUS



P.O. Box 245013
Milwaukee, WI 53224
(800) 776-7192
www.sharecorp.com



Do not breathe mist, spray. Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves. Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER.

Store locked up.

Dispose of contents/container to comply with local/regional/national/international regulations.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

NFPA* RATINGS:

Health: 2; Flammability: 0; Reactivity: 0

CONTAINS/CAS#:

Water/7732-18-5; Sodium Sulfite/7757-83-7;
Proprietary/Mixture; Potassium Carbonate/584-08-7;
Sodium Hydroxide/1310-73-2;
N,N-Diethylmonoethanolamine/100-37-8

0901.042715

TRIDENT BOILERPRO H PLUS is a multi-functional formula with all the necessary chemicals for a complete boiler treatment in one convenient liquid. It combines alkalinity builders and carbonate cycle scale control with oxygen scavengers, sludge dispersants and volatile amine corrosion inhibitors that travel with the steam to protect steam and condensate plumbing.

DIRECTIONS:

The dosage of **TRIDENT BOILERPRO H PLUS** will depend on the percent of condensate returned, makeup water characteristics and initial cleanliness of heat transfer surfaces. The treatment program must be accompanied by a program of regular blowdown to remove sludge and suspended solids from the boiler.

TRIDENT BOILERPRO H PLUS may be fed on a "one shot" basis or with an automated continuous system. Gradual and continuous feeding is recommended for large or industrial process boilers. **TRIDENT BOILERPRO H PLUS** may be mixed with other boiler treatment chemicals and diluted with water for convenient feeding. If the boiler water system has not been previously treated, add a starting dosage of twice the amount recommended for weekly dosages for the first four weeks.

For Weekly Maintenance: Add 1/2 gallon (2 quarts) of **TRIDENT BOILERPRO H PLUS** per week for each 25 horsepower of boiler capacity. This use rate may vary due to feedwater hardness and differences in a boiler's rated horsepower versus the boiler's operational horsepower.

Blowdown: Open the blowdown valve until the level drop in the sight glass is reached, recommended starting point is 2 inches twice a week. Blowdown schedules will vary depending upon water hardness and permissible cycles of concentration.



Please Recycle.

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com