

PO BOX 245013 MILWAUKEE, WI 53224 800.776.7192 www.sharecorp.com

DISPOSAL: Offer empty container for recycling. If recycling is not available, discard container in trash.

DIRECTIONS: Drain as much water as n ssible from hydrant. Fill hvdrant with YDRANT ANTI-FREEZE, leaving air iquid to expand and spac kont iging temperatures. HYDRANT ANTI-FREEZE is a food grade material that will ter supplies, but treated rinsed thoroughly before the water NFPA[®] RATINGS: burboses. Health: 0; Flammability: 1; Reactivity: 0 Undiluted: HYDRANT ANTI-FREEZE will protect hydrants down to -60°F.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.



NET CONTENTS: 0 1 0 5 0 20 0 35 0 55 Gallon(s)

HYDRANT ANTI-FREEZE is designed to prevent frost damage to exterior water hydrants. It is made with food grade ingredients to eliminate the possibility of contamination of potable water supplies. HYDRANT **ANTI-FREEZE** can also be used in radiators and all water cooled engines and can be tested with standard hydrometers.

Diluted: Use a 1:1 dilution ratio with water and HYDRANT ANTI-FREEZE will protect down to -25°F.

INGREDIENTS/CAS #: 1,2-propanediol (57-55-6)

