

SNOW CAP

White Elastomeric Coating

Form: Paste

Color: White liquid

Odor: Paint-like

pH: 9.0

Solubility (in water): Complete
(in mineral spirits): Insoluble

Viscosity (CPS at 70°F): N/D

Flash Point (ASTM D-7821): N/A

Specific Gravity: 10.6 lbs/gal

Density: 1.27 g/cm³

Storage Stability (at 70°F): 1 year

<u>Ingredients</u>	<u>C.A.S. #</u>
Water.....	7732-18-5
Calcium Carbonate.....	471-34-1
Titanium Dioxide.....	13463-67-7
Quartz.....	14808-60-7

Use to...
• Reduce Cooling Costs
• Extend Roof Life
• Reflect Harmful UV Rays
• Seal Roofs

DIRECTIONS: Surface and air temperatures must be a minimum of 50°F and rising. DO NOT apply if heavy dew or rain is expected within 24-48 hours. Apply on clear, sunny day in morning hours with a 3/4" nap exterior paint roller. First make repairs, then apply an initial coat over seams and joints. Allow to cure for one hour or until dry, then apply two (2) uniform coats over entire surface, avoiding excessive rolling. Two full coats are needed for all applications. Apply second coat perpendicular to first coat. Allow at least 24 hours between coats and 24-48 hours for full curing. DO NOT apply to flat surfaces, poor drainage areas, or where ponding water will exist. Coverage is approximately 50 – 100 ft² per gallon per coat.

HMIS			NFPA		
	Severe	4	Extreme		
Health	Serious	3	High	Health.....	1
Flammability.....	Moderate	2	Moderate	Flammability.....	0
Reactivity.....	Slight	1	Slight	Reactivity.....	0
Personal Protection.....	Minimal	0	Insignificant	Special Precautions.....	None