

Tar Remover



TAR & ASPHALT REMOVER, ODOR NEUTRALIZER AND DEGREASER

DANGER:

Flammable liquid and vapor. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Causes skin irritation.

See back panel for additional precautions.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: □ 1 □ 5 □ 20 □ 35 □ 55 Gallon(s)

Tar Remover



**PO BOX 245013
MILWAUKEE, WI 53224
800.776.7192
www.sharecorp.com**

TAR REMOVER is recommended for removal of road tar, asphalt, and grease from all municipal equipment. Regular applications are recommended for normal equipment maintenance. Effectively cleans boat and ship bilges. Removes sludge from oil tanks. Used by roofing contractors to clean tools and work areas. Also recommended for blacktop contractors for tool equipment maintenance.

DIRECTIONS:

Apply **TAR REMOVER** to the affected area, in concentrated form, with a 3 gallon pressure sprayer, or by mopping on the surface. Allow time to penetrate and dissolve the tar, asphalt or bituminous deposits for approximately 5 to 10 minutes; then rinse off with water under pressure. For light deposits of tar or asphalt, **TAR REMOVER** may be diluted with equal parts of an economical solvent such as mineral spirits. **NOTE:** Use with care on automotive finishes to prevent damage to air dried painted surfaces.

FOR USE AS CONCENTRATED ODOR CONTROL:

Sludge beds, land fills: Dilute 1 part of **TAR REMOVER** with 50 parts of water and spray to blow mist up wind from source of odor.

Application by drip method: It is not necessary to dilute **TAR REMOVER** in drip method application, as the flow will act as a dilutant. The quantity of drip required will depend upon the amount of odor and degree of control desired.

Garbage dumps, trucks and other areas where odors are persistent and concentrated in a relatively small area: Spray the whole area with undiluted **TAR REMOVER**. Spray as often as necessary, especially when adding untreated garbage to the truck or dump.

FOR USE AS ODOR CONTROL AND DEGREASER:

Sewage treatment: For odor control use 1 to 5 parts per million parts of sewage. Use 2% solution for daily spraying of filter beds.

Septic tanks, cesspools: Add 1 pint per 500 gallons of capacity for initial treatment. Use 1 to 2 ounces per week for each 500 gallons capacity as preventative maintenance treatment.

Garbage dumps, land fill areas, sludge aeration beds: Use 2 gallons of **TAR REMOVER** to each 100 gallons of water. Spray at a rate of 100 gallons of this solution for each 2000 to 3000 square feet of area to be treated.

Grease traps: Pour one-half cup (4 ounces) of **TAR REMOVER** into drain. Allow to remain overnight, if possible - at least two to four hours. **DO NOT ALLOW LIQUID OR VAPORS TO COME IN CONTACT WITH FOOD.**

INGREDIENTS/CAS#:

Monochlorotoluene (95-49-8)
Aliphatic hydrocarbon (64742-47-8)
Alkylphenol ethoxylate (127087-87-0)

NFPA® RATING:

Health: 2; Flammability: 2; Reactivity: 0



DANGER:

Flammable liquid and vapor. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure. Causes skin irritation. Harmful if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness.

PREVENTION:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. - No Smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling.

RESPONSE:

IF ON SKIN OR HAIR: Wash with plenty of water. Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. Call a POISON CENTER/doctor/physician if you feel unwell. Get medical advice/attention if you feel unwell.

STORAGE:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

DISPOSAL:

Dispose of contents/container in accordance with local/regional/national/international regulations.

For industrial and institutional use only.

For additional information, see Safety Data Sheet.

1325.021315