Safety Data Sheet



SECTION 1: Product and	co	mpany identification
Product name	:	Coil Cleaner
Use of the substance/mixture	:	Aerosol Cleaner
Product code	:	806101
Company	:	Share Corporation P.O. Box 245013 Milwaukee, WI 53224 - USA T (414) 355-4000
Emergency number	:	Chemtrec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Aerosol 1H222Eye Irrit. 2AH319Skin Sens. 1H317Full text of H-phrases: see section 16

2.2. Label elements	
GHS-US labeling	
Hazard pictograms (GHS-US) :	GHS02 GHS07
Signal word (GHS-US) :	Danger
Hazard statements (GHS-US) :	Extremely flammable aerosol May cause an allergic skin reaction Causes serious eye irritation
Precautionary statements (GHS-US) :	Keep away from heat, hot surfaces, Do not smoke, open flames, sparks No smoking Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use Avoid breathing gas Wash thoroughly after handling Contaminated work clothing must not be allowed out of the workplace Wear protective gloves, eye protection, face protection If on skin: Wash with plenty of water If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Specific treatment (see First aid measures on this label) If skin irritation or rash occurs: Get medical advice/attention If eye irritation persists: Get medical advice/attention Take off contaminated clothing and wash it before reuse Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F Dispose of contents/container to comply with local/regional/national/international regulations IF INHALED: Move to fresh air, If symptoms persist, call a physician If swallowed: Immediately call a POISON CENTER, a doctor, Do NOT induce vomiting

2.3. Other hazards No additional information available 2.4. Unknown acute toxicity (GHS US) Not applicable SECTION 3: Composition/information on ingredients 3.1. Substance Not applicable Full text of H-phrases: see section 16 3.2. Mixture



Safety Data Sheet

Name	Product identifier	%	Classification (GHS-US)
butane	(CAS No) 106-97-8	2.5 - 10	Flam. Gas 1, H220 Compressed gas, H280
Glycol Ether EB	(CAS No) 111-76-2	1 - 2.5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT RE 2, H373 Asp. Tox. 1, H304
propane	(CAS No) 74-98-6	1 - 2.5	Flam. Gas 1, H220 Compressed gas, H280
Diethylene Glycol Monoethyl Ether	(CAS No) 111-90-0	1 - 2.5	Acute Tox. 4 (Oral), H302 Eye Irrit. 2A, H319
tetrasodium ethylenediaminetetracetate	(CAS No) 64-02-8	1 - 2.5	Acute Tox. 4 (Oral), H302 Eye Dam. 1, H318
(+)-limonene	(CAS No) 5989-27-5	0.1 - 1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304
sodium nitrite	(CAS No) 7632-00-0	0.1 - 1	Ox. Sol. 3, H272 Acute Tox. 3 (Oral), H301 Eye Irrit. 2A, H319 Carc. 1B, H350

SECTION 4: First aid measures		
4.1. Description of first aid measures		
First-aid measures after inhalation	:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	:	Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. For minor skin contact, avoid spreading material on unaffected skin.
First-aid measures after eye contact	:	Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	:	Call a physician immediately.
4.2. Most important symptoms and effects,	bo	th acute and delayed
Symptoms/injuries	:	Causes serious eye irritation. May cause an allergic skin reaction. Extremely flammable.
Symptoms/injuries after inhalation	:	Irritation of the nasal mucous membranes.
Symptoms/injuries after skin contact	:	May cause an allergic skin reaction.
Symptoms/injuries after eye contact	:	Causes serious eye irritation.
Symptoms/injuries after ingestion	:	Not expected to present a significant ingestion hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting m	easures			
5.1. Extinguishing media				
Suitable extinguishing media	: Water.			
5.2. Special hazards arising from	the substance or mixture			
Fire hazard	: Extremely flamma	ble aerosol. Under fire conditions	closed containers may rupture or exp	olode.
Explosion hazard	: Contents under pr	essure. Pressurized container: ma	ay burst if heated.	
Reactivity	: Upon combustion:	CO and CO2 are formed.		
5.3. Advice for firefighters				
Firefighting instructions	: Exercise caution v be done without ri cargo area, use u burn out.	when fighting any chemical fire. Mo sk. Use water spray or fog for coo nmanned hose holder or monitor r	ove containers away from the fire area ling exposed containers. For massive nozzles, if possible. If not, withdraw an	a if this can e fire in nd let fire
Protection during firefighting	: Do not enter fire a	rea without proper protective equi	pment, including respiratory protectio	n.
SECTION 6: Accidental rele	ase measures			
6.1. Personal precautions, protec	tive equipment and emergency p	rocedures		
General measures	: Stay upwind/keep distances along g	distance from source. Evacuate u ound before igniting/flashing back	nnecessary personnel. Vapors may t to vapor source.	ravel long
6.1.1. For non-emergency perso	onnel			
Protective equipment	: Do not enter withon necessary. DO NO (basements, work	ut an appropriate protective equip DT touch spilled material. Ventilate pits etc.).	ment. Advice local authorities if cons the area thoroughly, especially low l	idered lying areas
Date of issue: 2/3/2016	Revision date: 02/03/2016	Version: 1.1	P GHS SDS	Page 2 of 8



Safety Data Sheet	CORP
Emergency procedures	: Do not breathe gas. Evacuate unnecessary personnel. Keep upwind. Ventilate spillage area.
6.1.2. For emergency responder	S
Protective equipment	: Equip cleanup crew with proper protection.
Emergency procedures	: Stop leak if safe to do so. Stop release. Ventilate area.
6.2. Environmental precautions	
Avoid release to the environment. A or its container. Prevent entry to se	Advice local authorities if considered necessary. Stop leak if safe to do so. Do not contaminate water with the product wers and public waters. Do not allow to enter drains or water courses.
6.3. Methods and material for con	tainment and cleaning up
For containment	: Eliminate every possible source of ignition. Prevent the product from entering drains or confined

		areas. Reep combustibles (wood, paper, oil, etc.) away from spilled material. Form with all vapors
		(heavier than air) who stay on the floor. Stop leak if safe to do so. Stop the leak. Turn leaking
		containers leak-side up to prevent the escape of liquid. Isolate area until gas has dispersed. Collect
		spillage.
Methods for cleaning up	:	Carefully collect the spill/leftovers. Clean contaminated surfaces with an excess of water. Dispose as hazardous waste.

6.4. Reference to other sections No additional information available

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed :	Do not use if spray button is missing or defective. Pressurized container: Do not pierce or burn, even after use. Keep away from heat, sparks and flame.
Precautions for safe handling :	Avoid prolonged and repeated contact with skin. Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal. Do not breathe gas/vapor/aerosol. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not spray on a naked flame or any incandescent material. Do not smoke while handling product. Ground/bond container and receiving equipment. Do not re-use empty containers. Avoid contact with skin and eyes. Use only outdoors or in a well-ventilated area. Observe normal hygiene standards. Wash hands and other exposed areas with mild soap and water before eat, drink or smoke and when leaving work. Do not discharge the waste into the drain.
Hygiene measures :	Wash thoroughly after handling.
7.2. Conditions for safe storage, including any	y incompatibilities
Technical measures :	Pressurized container. Do not puncture, incinerate or crush. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Storage conditions :	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep cool. Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50 °C/ 122 °F. Refrigerate.
Storage temperature :	< 49 °C
Storage area	Aerosol 1.

SECTION 8: Exposure controls/personal protection				
8.1. Control param	eters			
Glycol Ether EB (1	111-76-2)			
ACGIH	ACGIH TWA (ppm)	20 ppm		
ACGIH	Remark (ACGIH)	Eye & URT irr		
propane (74-98-6)				
ACGIH	ACGIH TWA (ppm)	1000 ppm		
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm		
butane (106-97-8)				
ACGIH	ACGIH TWA (ppm)	1000 ppm		

8.2. Exposure controls Appropriate engineering controls

ACGIH

: Ensure good ventilation of the work station.

ACGIH STEL (ppm)

1000 ppm

Safety Data Sheet

Personal protective equipment

SECTION 0. Develoal

: Gloves. Protective goggles. Protective clothing. Use appropriate personal protective equipment when risk assessment indicates this is necessary.



SECTION 7. Thysical and chemical p	nopernes
9.1. Information on basic physical and chem	ical properties
Physical state	: Gas
Appearance	: Aerosol. Clear, colorless liquid.
Odor	: characteristic
Odor threshold	: No data available
рН	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 212 °F Estimated
Flash point	: -156 °F Propellant estimated
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 0.969 g/ml
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available

SECTION 10: Stability and reactivity

10.1. Reactivity
Upon combustion: CO and CO2 are formed.
10.2. Chemical stability
Stable under normal conditions.
10.3. Possibility of hazardous reactions
No dangerous reactions known under normal conditions of use.
10.4. Conditions to avoid
Exposure to air.
10.5. Incompatible materials
oxygen. Do not mix with other chemicals. None known.
10.6. Hazardous decomposition products
Under normal conditions of storage and use, hazardous decomposition products should not be produced.
SECTION 11: Toxicological information
11.1. Information on toxicological effects

Acute toxicity

: Not classified



Safety Data Sheet



Glycol Ether EB (111-76-2)		
LD50 oral rat	1300 mg/kg	
LD50 dermal rat	> 2000 mg/kg	
ATE CLP (oral)	1300.000 mg/kg body weight	
ATE CLP (dermal)	1100.000 mg/kg body weight	
ATE CLP (dust, mist)	1.500 mg/l/4h	
(+)-limonene (5989-27-5)		
LD50 oral rat	4400 mg/kg body weight (Rat; OECD 423: Acute Oral Toxicity – Acute Toxic Class Method; Literature study; > 2000 mg/kg bodyweight; Rat; Read-across)	
LD50 dermal rabbit	> 5000 mg/kg body weight (Rabbit; Weight of evidence; Equivalent or similar to OECD 402)	
ATE CLP (oral)	4400.000 mg/kg body weight	
tetrasodium ethylenediaminetetracetate (64-02	2-8)	
LD50 oral rat	> 2000 mg/kg (Rat)	
ATE CLP (oral)	500.000 mg/kg body weight	
Diethylene Glycol Monoethyl Ether (111-90-0)		
LD50 oral rat	1920 mg/kg	
sodium nitrite (7632-00-0)		
ATE CLP (oral)	100.000 mg/kg body weight	
Skin corrosion/irritation :	Not classified.	
Serious eye damage/irritation :	Causes serious eye irritation.	
Respiratory or skin sensitization :	May cause an allergic skin reaction.	
Germ cell mutagenicity :	Not classified	
Carcinogenicity :	Not classified.	
Glycol Ether EB (111-76-2)		
IARC group	3 - Not Classifiable	
(+)-limonene (5989-27-5)		
IARC group	3 - Not Classifiable	
Reproductive toxicity :	Not classified	
Specific target organ toxicity (single exposure) :	Not classified	
Specific target organ toxicity (repeated : exposure)	Not classified.	
Glycol Ether EB (111-76-2)		
LOAEL (oral,rat,90 days)	69 mg/kg bodyweight/day Target organ: liver	
NOAEL (dermal,rat/rabbit,90 days)	150 mg/kg bodyweight/day	
Aspiration hazard	: Not classified	
Symptoms/injuries after inhalation	: Irritation of the nasal mucous membranes.	
Symptoms/injuries after skin contact	: May cause an allergic skin reaction.	
Symptoms/injuries after eye contact	: Causes serious eye irritation.	
Symptoms/injuries after ingestion	: Not expected to present a significant ingestion hazard under anticipated conditions of normal use.	
Likely routes of exposure	: Skin and eyes contact.;Inhalation	

SECTION 12: Ecological information	
12.1. Toxicity	
Glycol Ether EB (111-76-2)	
LC50 fish 1	1474 mg/l Oncorhynchus mykiss
EC50 Daphnia 1	100 mg/l Water flea
ErC50 (algae)	1840 mg/l Pseudokirchneriella subcapitata
NOEC chronic fish	> 100 mg/l
NOEC chronic crustacea	100 mg/l daphnid
(+)-limonene (5989-27-5)	
LC50 fish 1	720 μg/l (96 h; Pimephales promelas; Lethal)
EC50 Daphnia 1	0.36 mg/l (48 h; Daphnia magna; GLP)
LC50 fish 2	702 μg/l (96 h; Pimephales promelas)

Safety Data Sheet



(+)-limonene (5989-27-5)		
Threshold limit algae 1	150 mg/l (72 h; Desmodesmus subspicatus; GLP)	
Threshold limit algae 2	2.62 mg/l (72 h; Desmodesmus subspicatus)	
tetrasodium ethylenediaminetetracetate (64-02-8)		
LC50 fish 1	121 mg/l (96 h; Lepomis macrochirus; Soft water)	
EC50 Daphnia 1	625 mg/l (24 h; Daphnia magna)	
LC50 fish 2	374 - 792 mg/l (96 h; Lepomis macrochirus; pH > 7)	
Threshold limit algae 1	> 100 mg/l (72 h; Scenedesmus subspicatus; Growth)	
12.2. Persistence and degradability		
(+)-limonene (5989-27-5)		
Persistence and degradability	Readily biodegradable in water. Forming sediments in water. Adsorbs into the soil.	
ThOD	3.29 g O□/g substance	
tetrasodium ethylenediaminetetracetate (64-02-8)		
Persistence and degradability	Not readily biodegradable in water.	
Biochemical oxygen demand (BOD)	< 0.002 g O /g substance	
Chemical oxygen demand (COD)	0.54 - 0.58 g O□/g substance	
12.3. Bioaccumulative potential		
(+)-limonene (5989-27-5)		
BCF fish 1	864.8 - 1022 (Pisces; Fresh weight)	
Log Pow	 4.38 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 37 °C) 	
Bioaccumulative potential	Potential for bioaccumulation ($4 \ge Log \text{ Kow} \le 5$).	
tetrasodium ethylenediaminetetracetate (64-02-8)		
Log Pow	-2.6	
Bioaccumulative potential	Bioaccumulation: not applicable.	
SECTION 13: Disposal considerations		

13.1. Waste treatment methods	
Waste treatment methods	: Contents under pressure. Do not puncture, incinerate or crush.
Waste disposal recommendations	: Dispose of contents/container to comply with local/regional/national regulations.

SECTION 14: Transport information

Department of Transportation (DOT)		
Transport document description	:	UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1
UN-No.(DOT)	:	UN1950
Proper Shipping Name (DOT)	:	Aerosols
		flammable, (each not exceeding 1 L capacity)
Transport hazard class(es) (DOT)	:	2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
Hazard labels (DOT)	:	2.1 - Flammable gas
DOT Packaging Non Bulk (49 CFR 173.xxx)	:	None
DOT Packaging Bulk (49 CFR 173.xxx)	:	None
DOT Special Provisions (49 CFR 172.102)	:	N82
DOT Packaging Exceptions (49 CFR 173.xxx)	:	306
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	150 kg
DOT Vessel Stowage Location	:	A



Safety Data Sheet	CORP
DOT Vessel Stowage Other	 25 - Shade from radiant heat,87 - Stow "separated from" Class 1 (explosives) except Division 14,126 - Segregation same as for Class 9, miscellaneous hazardous materials
Additional information	
Other information	: This product may be eligible to be shipped as a Limited Quantity or Consumer Commodity ORM-D utilizing the exception found at 49 CFR 173.306.
ADR	
No additional information available	
Transport by sea	
UN-No. (IMDG)	: UN1950
Proper Shipping Name (IMDG)	: AEROSOLS
Class (IMDG)	: 2.1 - Flammable gases
Air transport	
UN-No.(IATA)	: UN1950
Proper Shipping Name (IATA)	: Aerosols, flammable
Class (IATA)	: 2.1 - Gases : Flammable
SECTION 15: Regulatory informati	on

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amndments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

sodium nitrite	CAS No 7632-00-0	0.1 - 1
Glycol Ether EB	CAS No 111-76-2	1 - 2.5

propane (74-98-6)	
Not listed on SARA Section 313 (Specific toxic ch	emical listings)
butane (106-97-8)	
Not listed on SARA Section 313 (Specific toxic ch	emical listings)
sodium nitrite (7632-00-0)	
Listed on SARA Section 313 (Specific toxic chemi	cal listings)
RQ (Reportable quantity, section 304 of EPA's List of Lists)	100 lb

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

SECTION 16: Other information

Training advice

: Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1B	Carcinogenicity Category 1B
Compressed gas	Gases under pressure Compressed gas
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Aerosol 1	Flammable aerosol Category 1
Flam. Gas 1	Flammable gases Category 1
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Ox. Sol. 3	Oxidizing solids Category 3
Skin Irrit. 2	Skin corrosion/irritation Category 2



Safety Data Sheet

Skin Sens. 1Skin sensitization Category 1STOT RE 2Specific target organ toxicity (repeated exposure) Category 2H220Extremely flammable gasH222Extremely flammable aerosolH226Flammable liquid and vaporH227Combustible liquidH272May intensify fire; oxidizerH280Contains gas under pressure; may explode if heatedH301Toxic if swallowedH302Harmful if swallowedH315Causes skin irritationH317May cause an allergic skin reactionH319Causes serious eye damageH313May cause damage to organs through prolonged or repeated exposure		
STOT RE 2Specific target organ toxicity (repeated exposure) Category 2H220Extremely flammable gasH222Extremely flammable aerosolH226Flammable liquid and vaporH227Combustible liquidH272May intensify fire; oxidizerH280Contains gas under pressure; may explode if heatedH301Toxic if swallowedH302Harmful if swallowedH304May be fatal if swallowed and enters airwaysH315Causes skin irritationH317May cause an allergic skin reactionH318Causes serious eye damageH350May cause cancerH373May cause damage to organs through prolonged or repeated exposure	Skin Sens. 1	Skin sensitization Category 1
H220Extremely flammable gasH222Extremely flammable aerosolH226Flammable liquid and vaporH227Combustible liquidH272May intensify fire; oxidizerH280Contains gas under pressure; may explode if heatedH301Toxic if swallowedH302Harmful if swallowedH304May be fatal if swallowed and enters airwaysH315Causes skin irritationH317May cause an allergic skin reactionH318Causes serious eye damageH350May cause cancerH373May cause damage to organs through prolonged or repeated exposure	STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
H222Extremely flammable aerosolH226Flammable liquid and vaporH227Combustible liquidH272May intensify fire; oxidizerH280Contains gas under pressure; may explode if heatedH301Toxic if swallowedH302Harmful if swallowedH304May be fatal if swallowed and enters airwaysH315Causes skin irritationH317May cause an allergic skin reactionH318Causes serious eye damageH350May cause cancerH373May cause damage to organs through prolonged or repeated exposure	H220	Extremely flammable gas
H226Flammable liquid and vaporH227Combustible liquidH272May intensify fire; oxidizerH280Contains gas under pressure; may explode if heatedH301Toxic if swallowedH302Harmful if swallowedH304May be fatal if swallowed and enters airwaysH315Causes skin irritationH317May cause an allergic skin reactionH318Causes serious eye damageH319Causes serious eye irritationH350May cause cancerH373May cause damage to organs through prolonged or repeated exposure	H222	Extremely flammable aerosol
H227Combustible liquidH272May intensify fire; oxidizerH280Contains gas under pressure; may explode if heatedH301Toxic if swallowedH302Harmful if swallowedH304May be fatal if swallowed and enters airwaysH315Causes skin irritationH317May cause an allergic skin reactionH318Causes serious eye damageH319Causes serious eye irritationH350May cause cancerH373May cause damage to organs through prolonged or repeated exposure	H226	Flammable liquid and vapor
H272May intensify fire; oxidizerH280Contains gas under pressure; may explode if heatedH301Toxic if swallowedH302Harmful if swallowedH304May be fatal if swallowed and enters airwaysH315Causes skin irritationH317May cause an allergic skin reactionH318Causes serious eye damageH319Causes serious eye irritationH350May cause cancerH373May cause damage to organs through prolonged or repeated exposure	H227	Combustible liquid
H280Contains gas under pressure; may explode if heatedH301Toxic if swallowedH302Harmful if swallowedH304May be fatal if swallowed and enters airwaysH315Causes skin irritationH317May cause an allergic skin reactionH318Causes serious eye damageH319Causes serious eye irritationH350May cause cancerH373May cause damage to organs through prolonged or repeated exposure	H272	May intensify fire; oxidizer
H301Toxic if swallowedH302Harmful if swallowedH304May be fatal if swallowed and enters airwaysH315Causes skin irritationH317May cause an allergic skin reactionH318Causes serious eye damageH319Causes serious eye irritationH350May cause cancerH373May cause damage to organs through prolonged or repeated exposure	H280	Contains gas under pressure; may explode if heated
H302Harmful if swallowedH304May be fatal if swallowed and enters airwaysH315Causes skin irritationH317May cause an allergic skin reactionH318Causes serious eye damageH319Causes serious eye irritationH350May cause cancerH373May cause damage to organs through prolonged or repeated exposure	H301	Toxic if swallowed
H304May be fatal if swallowed and enters airwaysH315Causes skin irritationH317May cause an allergic skin reactionH318Causes serious eye damageH319Causes serious eye irritationH350May cause cancerH373May cause damage to organs through prolonged or repeated exposure	H302	Harmful if swallowed
H315Causes skin irritationH317May cause an allergic skin reactionH318Causes serious eye damageH319Causes serious eye irritationH350May cause cancerH373May cause damage to organs through prolonged or repeated exposure	H304	May be fatal if swallowed and enters airways
H317May cause an allergic skin reactionH318Causes serious eye damageH319Causes serious eye irritationH350May cause cancerH373May cause damage to organs through prolonged or repeated exposure	H315	Causes skin irritation
H318 Causes serious eye damage H319 Causes serious eye irritation H350 May cause cancer H373 May cause damage to organs through prolonged or repeated exposure	H317	May cause an allergic skin reaction
H319 Causes serious eye irritation H350 May cause cancer H373 May cause damage to organs through prolonged or repeated exposure	H318	Causes serious eye damage
H350 May cause cancer H373 May cause damage to organs through prolonged or repeated exposure	H319	Causes serious eye irritation
H373 May cause damage to organs through prolonged or repeated exposure	H350	May cause cancer
exposure	H373	May cause damage to organs through prolonged or repeated
		exposure

NFPA health hazard	:	2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA fire hazard	:	2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.
NFPA reactivity	:	0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.