

SNOW PRO

Siliconized Snowplow Coating Spray

Form: Aerosol Liquid

Color: Colorless

Odor: Solvent

pH: N/A

Solubility (in water): Insoluble
(in mineral spirits): Soluble

VOC Content (% by weight): ~97.0%

Flash Point (ASTM D-7821): 0°F

Specific Gravity: 0.77 g/cm³

Density: 6.43 lbs/gal

<u>Ingredients</u>	<u>C.A.S. #</u>
Heptane	142-82-5
N-Butane (propellant)	106-97-8
Propane (propellant)	74-98-6
Silicone Fluid	68952-01-2

SNOW PRO Also...

- **Provides a release coating for salt equipment**
- **Lubricates critical control points**
- **Lubricates rubber door & window seals**
- **Prevents freezing of locks**
- **Provides a release coating for shovels and road signs**
- **May be applied to almost any surface**

DIRECTIONS:

Pre-clean all surfaces to be treated. Hold aerosol can 8” to 10” from surface. Spray SNOW PRO lightly with a side-to-side sweeping motion. Avoid over spraying. Wipe off excess with a clean cloth and buff lightly to set the “slick” coating. To lubricate sticking parts, work the part back and forth while applying SNOW PRO, to allow good penetration.

HMIS			NFPA		
	Severe	4	Extreme		
Health	Serious	3	High	Health	2
Flammability	Moderate	2	Moderate	Flammability	4
Reactivity	Slight	1	Slight	Reactivity	0
Personal Protection	Minimal	0	Insignificant	Special Precautions	None