

# Guardian

## Penetrating Lube

**Form:** Liquid

**Color:** Hazy Yellow Liquid

**Odor:** Acetate

**pH:** N/A

**Solubility (in water):** Insoluble  
**(in mineral spirits):** Soluble

**VOC Content (% by weight):** 19.7

**Flash Point (ASTM D-7821):** N/D

**Specific Gravity:** 0.79 g/cm<sup>3</sup>

**Density:** 6.59 lbs/gal

**Storage Stability (at 70°F):** 1 year

**Ingredients**

**C.A.S. #**

Hydrotreated Heavy Naphthenic	
Petroleum Distillate .....	64742-52-5
C13-C16 Isoalkanes .....	68551-20-2
Spectrasyn 10 TDS.....	Mixture
Propane/n-Butane.....	68476-86-8
Methyl Acetate.....	79-20-9
Butyl Acetate.....	123-86-4

**Great for...**

- Mechanics
- Pipefitters
- Plumbers
- Assemblers
- Maintenance personnel

**Provides protection for...**

- Rifles
- Fishing reels
- Cables
- Parts
- Fire hydrants
- Lock mechanisms
- Movable parts
- Cutting tables
- Hinges
- Pulleys
- Springs
- Chain drives

**DIRECTIONS:** Shake well before using. Hold nozzle 6 to 8 inches from surface to be treated. Saturate area with GUARDIAN. Severely corroded parts may need additional treatment. Reapply as necessary.

HMIS®				NFPA®	
		Severe	4	Extreme	
Health .....	1	Serious	3	High	Health .....
Flammability.....	3	Moderate	2	Moderate	Flammability.....
Reactivity.....	0	Slight	1	Slight	Reactivity.....
Personal Protection.....	X	Minimal	0	Insignificant	Special Precautions.....
					None