

# Penetrating Oil Aerosol

## Safety Data Sheet



### SECTION 1: Product and company identification

Product name : Penetrating Oil Aerosol  
Use of the substance/mixture : Aerosol  
Lubricant.  
Product code : 810001  
Company : Share Corporation  
P.O. Box 245013  
Milwaukee, WI 53224 - USA  
T (414) 355-4000  
Emergency number : Chemtrec: (800) 424-9300

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (GHS-US)

Flam. Aerosol 1 H222  
Liquefied gas H280  
Skin Irrit. 2 H315  
Eye Irrit. 2A H319  
Skin Sens. 1B H317  
Muta. 2 H341  
Carc. 1B H350  
STOT SE 3 H336  
Asp. Tox. 1 H304

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Extremely flammable aerosol  
Contains gas under pressure; may explode if heated  
May be fatal if swallowed and enters airways  
Causes skin irritation  
May cause an allergic skin reaction  
Causes serious eye irritation  
May cause drowsiness or dizziness  
Suspected of causing genetic defects (Inhalation)  
May cause cancer (Inhalation)

Precautionary statements (GHS-US) :

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Keep away from heat, sparks, open flames, hot surfaces, Do not smoke. - No smoking  
Do not spray on an open flame or other ignition source  
Pressurized container: Do not pierce or burn, even after use  
Avoid breathing mist, spray  
Wash thoroughly after handling  
Use only outdoors or in a well-ventilated area  
Contaminated work clothing must not be allowed out of the workplace  
Wear protective gloves, eye protection  
If swallowed: Immediately call a doctor, a POISON CENTER, Do NOT induce vomiting  
If on skin: Wash with plenty of soap and water  
If inhaled: Remove person to fresh air and keep comfortable for breathing  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If exposed or concerned: Get medical advice/attention  
Call a POISON CENTER, a doctor if you feel unwell  
Do NOT induce vomiting  
If skin irritation or rash occurs: Get medical advice/attention  
If eye irritation persists: Get medical advice/attention  
Take off contaminated clothing and wash it before reuse  
Store in a well-ventilated place. Keep container tightly closed

# Penetrating Oil Aerosol

## Safety Data Sheet



Store locked up  
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F  
Dispose of contents/container to comply with local/regional/national/international regulations

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

Full text of H-phrases: see section 16

### 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
trichloroethylene, trichloroethene	(CAS No) 79-01-6	30 - 40	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Muta. 2, H341 Carc. 1B, H350 STOT SE 3, H336 Aquatic Chronic 3, H412
kerosine (petroleum)	(CAS No) 8008-20-6	20 - 30	Flam. Liq. 3, H226
Distillates (petroleum), solvent-refined heavy paraffinic	(CAS No) 64741-88-4	10 - 20	Carc. 1B, H350
Distillates (petroleum), light distillate hydrotreating process, low-boiling	(CAS No) 68410-97-9	5 - 10	Not classified
carbon dioxide, liquefied, under pressure	(CAS No) 124-38-9	1 - 5	Not classified

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Immediately call a poison center or doctor/physician. Vomiting: prevent asphyxia/aspiration pneumonia.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Extremely flammable. Contents under pressure. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. May cause cancer (Inhalation). Suspected of causing genetic defects (Inhalation). Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction.
Symptoms/injuries after inhalation	: Harmful if inhaled.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Water fog. Foam.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable aerosol. Under fire conditions closed containers may rupture or explode.
Explosion hazard	: Contains gas under pressure; may explode if heated. Vapors may travel long distances along ground before igniting/flashing back to vapor source.
Reactivity	: Upon combustion: CO and CO2 are formed.

### 5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment.

# Penetrating Oil Aerosol

## Safety Data Sheet



### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate unnecessary personnel. Isolate from fire, if possible, without unnecessary risk. Gas is denser than air. May accumulate in low areas e.g. close to the ground.

##### 6.1.1. For non-emergency personnel

Protective equipment : Do not enter without an appropriate protective equipment.

##### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.  
Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Do not allow to enter drains or water courses.

#### 6.3. Methods and material for containment and cleaning up

For containment : Stop leak if safe to do so. Isolate area until gas has dispersed. Eliminate every possible source of ignition. Use water spray to disperse the vapors. Collect spillage.  
Methods for cleaning up : Take up liquid spill into inert absorbent material.

#### 6.4. Reference to other sections

No additional information available

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use.  
Precautions for safe handling : Avoid contact with skin, eyes and clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container: Do not pierce or burn, even after use.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Do not puncture, incinerate or crush.  
Storage conditions : Do not expose to temperatures exceeding 50 °C/ 122 °F.  
Heat-ignition : KEEP SUBSTANCE AWAY FROM: ignition sources. heat sources.  
Storage area : Store in a cool area. Store away from heat.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

trichloroethylene, trichloroethene (79-01-6)		
ACGIH	ACGIH TWA (ppm)	10 ppm
ACGIH	ACGIH STEL (ppm)	25 ppm
ACGIH	Remark (ACGIH)	CNS impair; cognitive decrements
kerosine (petroleum) (8008-20-6)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup> (Kerosene/Jet fuels, as total hydrocarbon vapor; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Application restricted to conditions in which there are negligible aerosol exposures)
carbon dioxide, liquefied, under pressure (124-38-9)		
ACGIH	ACGIH TWA (ppm)	5000 ppm (Carbon dioxide; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	ACGIH STEL (ppm)	30000 ppm (Carbon dioxide; USA; Short time value; TLV - Adopted Value)

#### 8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.  
Personal protective equipment : Protective goggles. Safety glasses.



# Penetrating Oil Aerosol

## Safety Data Sheet



### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Aerosol. clear. Colorless liquid.
Odor	: Solvent-like odour
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: < 60 °F (liquid portion)
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1 g/ml
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: < 20 cSt
Viscosity, dynamic	: No data available
VOC content	: 79 %

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Upon combustion: CO and CO<sub>2</sub> are formed.

#### 10.2. Chemical stability

The product is stable at normal handling- and storage conditions.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

#### 10.4. Conditions to avoid

No flames, No sparks. Eliminate all sources of ignition.

#### 10.5. Incompatible materials

Alkalis. Oxidizing agent. aluminum. lithium.

#### 10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide. HCl.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>kerosine (petroleum) (8008-20-6)</b>	
LD50 oral rat	> 5000 mg/kg body weight (Rat; OECD 420: Acute Oral toxicity – Acute Toxic Class Method; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	> 5.28 mg/l/4h (Rat; Experimental value)

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

# Penetrating Oil Aerosol

## Safety Data Sheet



Respiratory or skin sensitization : May cause an allergic skin reaction.  
 Germ cell mutagenicity : Suspected of causing genetic defects (Inhalation).  
 Carcinogenicity : May cause cancer (Inhalation).

<b>trichloroethylene, trichloroethene (79-01-6)</b>	
IARC group	2A - Probably Carcinogenic to Humans
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen

<b>kerosine (petroleum) (8008-20-6)</b>	
IARC group	3 - Not Classifiable

Reproductive toxicity : Not classified.  
 Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.  
 Specific target organ toxicity (repeated exposure) : Not classified  
 Aspiration hazard : May be fatal if swallowed and enters airways.  
 Symptoms/injuries after inhalation : Harmful if inhaled.  
 Symptoms/injuries after skin contact : Causes skin irritation.  
 Symptoms/injuries after eye contact : Causes serious eye irritation.  
 Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.  
 Likely routes of exposure : Dermal;Inhalation

### SECTION 12: Ecological information

#### 12.1. Toxicity

kerosine (petroleum) (8008-20-6)	
LC50 fish 1	2-5,LL50; OECD 203: Fish, Acute Toxicity Test; 96 h; Oncorhynchus mykiss; Semi-static system; Fresh water; Experimental value
EC50 Daphnia 1	1.4 mg/l (EL50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 1	1-3,EL50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value
Threshold limit algae 2	1 mg/l (NOEL; OECD 201: Alga, Growth Inhibition Test; 48 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)

carbon dioxide, liquefied, under pressure (124-38-9)	
LC50 fish 1	35 mg/l (LC50; 96 h; Salmo gairdneri)

#### 12.2. Persistence and degradability

kerosine (petroleum) (8008-20-6)	
Persistence and degradability	Biodegradable in water. No significant hydrolysis. Adsorbs into the soil.
carbon dioxide, liquefied, under pressure (124-38-9)	
Persistence and degradability	Biodegradability: not applicable. Not applicable (gas).
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

#### 12.3. Bioaccumulative potential

kerosine (petroleum) (8008-20-6)	
Bioaccumulative potential	No test data available.
carbon dioxide, liquefied, under pressure (124-38-9)	
Log Pow	0.83 (Experimental value)
Bioaccumulative potential	Bioaccumulation: not applicable.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container to comply with local/regional/national/international regulations.

### SECTION 14: Transport information

#### Department of Transportation (DOT)

# Penetrating Oil Aerosol

## Safety Data Sheet



Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1  
 UN-No.(DOT) : UN1950  
 Proper Shipping Name (DOT) : Aerosols  
 flammable, (each not exceeding 1 L capacity)  
 Transport hazard class(es) (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115  
 Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : None  
 DOT Packaging Bulk (49 CFR 173.xxx) : None  
 DOT Special Provisions (49 CFR 172.102) : N82  
 DOT Packaging Exceptions (49 CFR 173.xxx) : 306  
 DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg  
 DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg  
 DOT Vessel Stowage Location : A  
 DOT Vessel Stowage Other : 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

### Additional information

Other information : No supplementary information available.

### ADR

No additional information available

### Transport by sea

No additional information available

### Air transport

No additional information available

## SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

trichloroethylene, trichloroethene	CAS No 79-01-6	30 - 40
------------------------------------	----------------	---------

trichloroethylene, trichloroethene (79-01-6)	
Listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	100 lb

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

## SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1B	Carcinogenicity Category 1B
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Aerosol 1	Flammable aerosol Category 1
Flam. Liq. 3	Flammable liquids Category 3

# Penetrating Oil Aerosol

## Safety Data Sheet




Liquefied gas	Gases under pressure Liquefied gas
Muta. 2	Germ cell mutagenicity Category 2
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1B	Skin sensitization Category 1B
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H222	Extremely flammable aerosol
H226	Flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects
H350	May cause cancer
H412	Harmful to aquatic life with long lasting effects

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.*