

LUBRI-GEL

Aerosol PTFE Resin Grease

Form: Aerosol Gel

Color: Amber

Odor: Solvent

pH: N/A

Solubility (in water): Insoluble
(in mineral spirits): Soluble

Viscosity (CPS at 70°F): >40

Flash Point (ASTM D-7821): 142°F

Specific Gravity: 0.70 g/cm³

Density: 5.84 lbs/gal

Storage Stability (at 70°F): 1 year

<u>Ingredients</u>	<u>C.A.S. #</u>
Hexane	110-54-3
Alkane Mixture (propellant)	74-98-6
Petrolatum	8009-03-8
Paraffinic Distillates.....	64742-65-0
Aliphatic Hydrocarbon.....	64742-63-8

Other Uses...	
•	Drawers
•	Hinges
•	Springs
•	Pulleys
•	Windows
•	Chain Drives
•	Locks
•	Cables
•	Pumps

DIRECTIONS: Shake well before using and during use. Apply to a clean, dry surface. Saturate the area to be lubricated. When applying to hard-to-reach areas, use an extension tube.

HMIS				NFPA	
		Severe	4	Extreme	
Health	2	Serious	3	High	Health..... 2
Flammability.....	4	Moderate	2	Moderate	Flammability..... 4
Reactivity.....	0	Slight	1	Slight	Reactivity..... 0
Personal Protection.....	X	Minimal	0	Insignificant	Special Precautions..... None