



# RUST CONVERTER

# RUST CONVERTER

## HALTS EXISTING RUST AND PREVENTS FUTURE CORROSION WITH A DURABLE PROTECTIVE BARRIER

No sand blasting, grinding or scraping required.

### DANGER:

Extremely Flammable Aerosol.  
Causes serious eye irritation.  
May cause drowsiness or dizziness.

### KEEP OUT OF REACH OF CHILDREN

See additional cautions on back panel.

**NET WEIGHT:** 13 Oz. (369 g)

**RUST CONVERTER** surface conditioner and primer changes rust into a dark, protective polymeric coating. It converts existing rust to an inert coating that seals out moisture to prevent future rust and corrosion. **RUST CONVERTER** provides an excellent primer coating for the application of quality oil-based paints. Surfaces protected with this primer and an oil-based paint resist the effects of weather, rain, sun and salt spray without peeling or cracking. This easy-to-use product is the first step in providing long-term protection of steel and iron surfaces.



### DANGER:

Extremely Flammable Aerosol. Causes serious eye irritation. May cause drowsiness or dizziness.

### PREVENTION:

Keep away from heat, hot surfaces, Do not smoke, open flames, sparks. - No smoking  
Do not spray on an open flame or other ignition source. Pressurized container:  
Do not pierce or burn, even after use.  
Avoid breathing dust, fume, gas, mist, spray, vapors. Wash thoroughly after handling.  
Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection, face protection.

### RESPONSE:

**IF INHALED:** Remove person to fresh air and keep comfortable for breathing  
**IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
Call a doctor, a POISON CENTER if you feel unwell.  
**If eye irritation persists:** Get medical advice/attention

### STORAGE:

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

### DISPOSAL:

Dispose of contents/container to comply with local/regional/national/international regulations.

### INGREDIENTS/CAS#:

Acetone, propan-2-one, propanone (67-64-1); Isobutane (75-28-5); Dimethyl ether (115-10-6); Ethanediol, ethylene glycol (107-21-1); Tannic acid (1401-55-4); 2-propanol (67-63-0)

### NFPA® RATINGS:

Health: 2; Flammability: 4; Reactivity: 0

### DIRECTIONS:

**SURFACE PREPARATION:** Remove large rust and scale particles with a wire brush or sandpaper. Clean the surface thoroughly to remove dirt, dust and grease.

**APPLICATION: SHAKE WELL BEFORE USING.** Do not apply if the surface temperature is below 50°F or above 90°F. Hold can 8-12 inches from surface and spray a thin, even coat onto the surface.

**DRYING TIME:** The resulting coat will dry to a smooth, dark finish in 20 minutes. Apply a second coat to ensure complete transformation of rusty surfaces, while protecting it from rain and dew. Allow 48 hours of cure time before the application of the finished paint coat.

For a long-lasting protection of treated surfaces, the cured **RUST CONVERTER** coating should be sealed with two coats of a high-quality oil-based paint. No other primer is required.

Sold by:

8346.060115