

# PAINT STRIPPER AEROSOL

## Paint & Varnish Remover Spray

**Form:** Gel Liquid

**Color:** Clear to Opaque

**Odor:** Sweet Solvent

**pH:** N/A

**Solubility (in water):** Slight  
**(in mineral spirits):** Soluble

**VOC Content (% by weight):** 39.8%

**Flash Point (ASTM D-7821):** -75°F (conc.)

**Specific Gravity:** 1.13 g/cm<sup>3</sup>

**Density:** 9.43 lbs/gal

**Ingredients**

**C.A.S. #**

Methylene Chloride .....	75-09-2
Liquid Petroleum Gas .....	68476-86-8
Toluene .....	108-88-3
Ethanol .....	64-17-5
Methanol .....	67-56-1

**Use As...**

- **Concrete Seal Remover**
- **Gasket Remover**
- **Graffiti Remover**
- **Gym Floor Stripper**

**Safe On...**

- **Iron**
- **Steel**
- **Brass**
- **Brick**
- **Concrete**
- **Wood**
- **Aluminum**

**DIRECTIONS:** Spray PAINT STRIPPER AEROSOL uniformly over the surface to be stripped. Strip only a small section at a time. Allow PAINT STRIPPER AEROSOL to penetrate and soften paint for 5 to 15 minutes. On thicker paint, a second application may be necessary for complete removal. Remove softened paint with a scraper, putty knife, cloth or strong water spray. PAINT STRIPPER is also water flushable. Wipe the treated surface clean and allow to dry before repainting.

HMIS				NFPA	
		Severe	4	Extreme	
Health .....	3	Serious	3	High	Health..... 3
Flammability.....	3	Moderate	2	Moderate	Flammability..... 3
Reactivity.....	1	Slight	1	Slight	Reactivity..... 1
Personal Protection.....	X	Minimal	0	Insignificant	Special Precautions.....None